




# BEARING CORP.OF CANADA LTD.



## 35 mm x 62 mm x 14 mm SKF S7007 CD/P4A Angular contact ball bearings

Bearing No. S7007 CD/P4A

S7007 CD/P4A Bearing 2D drawings and 3D CAD models

Size	62x35x14 mm
Bore Diameter	62 mm
Outer Diameter	35 mm
Width	14 mm
d	35 mm
D	62 mm
B	14 mm
d <sub>1</sub>	43.7 mm
d <sub>2</sub>	43.7 mm
D <sub>2</sub>	55.57 mm
r <sub>1,2</sub> - min.	1 mm
r <sub>3,4</sub> - min.	0.3 mm
a	13.6 mm
d <sub>a</sub> - min.	39.6 mm
d <sub>a</sub> - max.	43.2 mm
d <sub>b</sub> - min.	39.6 mm
d <sub>b</sub> - max.	43.2 mm
D <sub>a</sub> - max.	57.4 mm
D <sub>b</sub> - max.	60 mm
r <sub>a</sub> - max.	1 mm
r <sub>b</sub> - max.	0.3 mm
Basic dynamic load rating - C	15.6 kN
Basic static load rating - C <sub>0</sub>	9.5 kN
Fatigue load limit - P <sub>u</sub>	0.4 kN



## BEARING CORP.OF CANADA LTD.

Limiting speed for grease lubrication	24000 r/min
Ball - $D_w$	7.938 mm
Ball - z	16
Calculation factor - $f_0$	9.7
Preload class A - $G_A$	60 N
Preload class B - $G_B$	120 N
Preload class C - $G_C$	240 N
Preload class D - $G_D$	480 N
Calculation factor - f	1.06
Calculation factor - f	1
Calculation factor - $f_{2A}$	1
Calculation factor - $f_{2B}$	1.02
Calculation factor - $f_{2C}$	1.05
Calculation factor - $f_{2D}$	1.09
Calculation factor - $f_{HC}$	1
Preload class A	36 N/micron
Preload class B	47 N/micron
Preload class C	64 N/micron
Preload class D	90 N/micron
$d_1$	43.7 mm
$d_2$	43.7 mm
$D_2$	55.57 mm
$r_{1,2}$ min.	1 mm
$r_{3,4}$ min.	0.3 mm
$d_a$ min.	39.6 mm
$d_a$ max.	43.2 mm
$d_b$ min.	39.6 mm
$d_b$ max.	43.2 mm
$D_a$ max.	57.4 mm
$D_b$ max.	60 mm



## BEARING CORP.OF CANADA LTD.

$r_a$ max.	1 mm
$r_b$ max.	0.3 mm
Basic dynamic load rating C	15.6 kN
Basic static load rating $C_0$	9.5 kN
Fatigue load limit $P_u$	0.4 kN
Attainable speed for grease lubrication	24000 r/min
Ball diameter $D_w$	7.938 mm
Number of balls z	16
Preload class A $G_A$	60 N
Static axial stiffness, preload class A	36 N/ $\mu$ m
Preload class B $G_B$	120 N
Static axial stiffness, preload class B	47 N/ $\mu$ m
Preload class C $G_C$	240 N
Static axial stiffness, preload class C	64 N/ $\mu$ m
Preload class D $G_D$	480 N
Static axial stiffness, preload class D	90 N/ $\mu$ m
Calculation factor f	1.06
Calculation factor $f_1$	1
Calculation factor $f_{2A}$	1
Calculation factor $f_{2B}$	1.02
Calculation factor $f_{2C}$	1.05
Calculation factor $f_{2D}$	1.09
Calculation factor $f_{HC}$	1
Calculation factor $f_0$	9.7
Mass bearing	0.15 kg